



MODEL NO.	L	W	Ds	Hs	Db	Hb
C63-XX10-10/12	33	18	10	56	18	33
C63-XX20-10/12	36	18	12	61	18	40
C63-XX25-10/12	37	18	13	63	18	40
C63-XX30-10/12	38	18	14	73	18	40
C63-XX40-10/12	46	24	16	73	24	41
C63-XX50-10/12	48	24	18	75	24	50

XX = (AK) DEALKALIZER  
 (SU) SULFATE  
 (TN) TANNIN

NOTES:

- 1) VALVE INLET AND OUTLET CONNECTIONS ARE 1" OR 1-1/4" NPTF.
- 2) VALVE DRAIN CONNECTION IS 3/4" OR 1" NPTF.
- 3) PIPE AND FITTINGS ARE NOT FURNISHED.
- 4) IT IS RECOMMENDED THAT FLEXIBLE CONNECTORS BE INSTALLED BETWEEN HARD PIPING AND VALVE INLET AND OUTLET CONNECTIONS.
- 5) THE TANK MANUFACTURER RESERVES THE RIGHT TO INVALIDATE THE TANK WARRANTY IF FLEXIBLE CONNECTORS ARE NOT INSTALLED PER NOTE 4.

SCALE	NTS	LAYOUT DRAWING C63 SERIES - 1 & 1-1/4" SINGLE 	DRAWING NO.	C63 1 & 1-1/4" SINGLE	REV.
DATE	10-21-17		DRAWN GRBauer CHKD GRB APP'D. GRB		SHEET 1 OF 1
DRAWN	GRBauer				
CHKD	GRB				
APP'D.	GRB				